

Packaged Window Heat Pump




Technical Product Sheet

Product Highlights

- Highly efficient 9.5K/9K (Cooling/Heating) BTU package windowmounted heat pump(PWHP) from the world's #1 air treatment brand
- Cold climate inverter heat pump technology with operation down to -22°F
- Adjustable saddle-style construction to work with various window and wall construction types
- Pivoting outdoor section with included liftassisted mounting bracket for easy installation
- No auxiliary resistance electric heater
- Self-contained condensate management system that does not require condensate drain/plumbing
- Compatible with standard 15A-115VAC outlet
- Models available with with wireless mesh BACnet capability or Wi-Fi
- Quiet Operation
- R-32 refrigerant
- Limited Warranty: 2 year full (5 year functional and sealed system parts; 12 year compressor)

Email: pwhpsales@midea.com

Minimum Window Dimensions



	Outdoor Condition	Capacity (BTU/Hr)	Efficiency
Cooling Mode	95°F (35°C)	9500	12.4
Heating Mode	47°F (8.3°C)	9000	4.05
	17°F (35°C)	9000	2.5
	5°F (-15°C)	9000	2.08
Min Temp	-13°F (-25°C)	6200	1.41
CEER		17.6	
HEER		11.0	
Indoor Sound	HIGH	LOW	SILENT
Power Level	57	47	39
Unit Weight		127.2	

